Responding to the First Impervious Cover-Based TMDL:

Lessons from the Field





The Eagleville Brook Story

- Birth of the IC-TMDL
- The lucky watershed
- Can it be done?
- Implications for others

















Birth of the IC-TMDL

 The maximum amount of a pollutant a waterbody can receive without adverse impact to designated uses

 Under section 303(d) of the Federal Clean Water Act (CWA), states are required to develop TMDLs for impaired waters

 The end result is a Water Quality Management Plan with quantitative pollutant load reduction targets

 Generally expressed as pollutant concentration targets, % reductions in pollutant levels, or mass load reductions

Connecticut Probable Sources of Impairments for Threatened and Impaired Rivers and Streams Reporting Year 2006

Description of this table

	Description of this table	-
Probable Source	Probable Source Group	
Source Unknown	Unknown	
Unspecified Urban Stormwater	Urban-Related Runoff/Stormwater	
Municipal Point Source Discharges	Municipal Dishcarges/Sewage	
Sources Outside State Juristiction Or Borders	Other	
Industrial Point Source Discharge	Industrial	
Combined Sewer Overflows	Municipal Dishcarges/Sewage	8
Landfills	Land Application/Waste Sites/Tanks	49
Contaminated Sediments	Legacy/Historical Pollutants	49
Sanitary Sewer Overflows (Collection System Failures)	Municipal Dishcarges/Sewage	47
Impacts From Hydrostructure Flow Regulation/Modification	Hydromodification	42
Upstream Impoundments (E.G., Pl-566 Nrcs Structures)	Hydromodification	41
Channelization	Hydromodification	39
Site Clearance (Land Development Or Redevelopment)	Construction	38
Baseflow Depletion From Groundwater Withdrawals	Hydromodification	32
Agriculture	Agriculture	29
Above Ground Storage Tank Leaks (Tank Farms)	Spills/Dumping	25
Flow Alterations From Water Diversions	Hydromodification	24
Golf Courses	Recreation And Tourism (Non-Boating)	22
Dredge Mining	Resource Extraction	16
Loss Of Riparian Habitat	Habitat Alterations (Not Directly Related To Hydromodification)	15
Animal Feeding Operations (Nps)	Agriculture	13
Livestock (Grazing Or Feeding Operations)	Agriculture	10
Waterfowl	Natural/Wildlife	9

 CTDEP developed a method to address impairments caused by storm water runoff using impervious cover

393

Miles Threatened or Impaired

132

107 105


> Eagleville Brook was the first location to get an impervious cover TMDL



Why Impervious Cover?


DEP Stressor ID Study identified a complex array of pollutants generated from storm water runoff as most probable cause of impairment

- Simplifies complex impacts but based on good science
- Good correlation between IC and stream health
- IC data available statewide
- Measurable and generated by local land use
- We can do something about better land use decisions and stormwater







Linking the Bugs to IC



% of Reference Community compares 7 metrics- Taxa Richness, Modified HBI, Scraper/Filterer, EPT/Chironomidae, % Dominant Taxa, EPT Index, Community Loss










Why Focus on Eagleville Brook?

- Listed on <u>CT 2002 Impaired</u> <u>Waters List</u>
- Does not meet aquatic life use goals – Cause Unknown
- In-stream biology severely impacted
- Visible impacts from sedimentation and altered flow



3100-19-2-R1

3100-19-1



3100-19-1-13

Eagleville Brook IC-TMDL

1				Pero	Percent Impervious Cover			
Л	Waterbody Name	Map	Waterbody	TMDL	WLA	MOS	Current	TMDL
	and Segment ID	ID	Segment	Target	and		Condition	Implementation
	The same of the sa		Description		LA			Objective
	Eagleville Brook_01 CT 3100-19_01	1	From the mouth at Eagleville Pond upstream to confluence with Kings Brook, Mansfield.	12 %	11%	1%	5 %	Anti-degradation
	Eagleville Brook_02 CT 3100-19_02 (Map ID 2)	2	From confluence with Kings Brook to headwaters near UCONN campus.	12 %	11%	1%	14 %	21 % Reduction in % IC accomplished by improved stormwater management
	Eagleville Brook_02 CT 3100-19_02 (Map ID 3)	3	Unnamed Pond on UCONN Campus (contained within CT 3100-19_02)	12 %	11%	1%	27%	59 % Reduction in % IC accomplished by improved stormwater management



Eagleville Brook IC-TMDL

TMDL Target is 12% IC; where

11% IC = WLA + LA

1% = Margin Of Safety


12%

- Expressed as % reduction in IC per subbasin
- IC used as surrogate for "complex array of pollutants transported by stormwater runoff"
- Success measured by assessing aquatic life, but interim progress may be measured by reducing the impacts of IC

Goal <u>Is Not</u> to reduce the % IC in the watershed per se, but to reduce the <u>impact</u> of IC through <u>stormwater management</u> to levels equivalent to < 11% IC.



Implementation Strategies



- 1. Reduce IC where practical (i.e., remove or replace with pervious surfaces)
- 2. Disconnect IC from surface waterbody (e.g., disconnect roofs)
- 3. Minimize additional disturbance to natural areas
- 4. Retrofit with distributed BMPs to reduce runoff volumes & improve water quality
- 5. Increase tree canopy cover and restore permeability of open areas



Can it be done???

1. Mapping Analysis

 Actual IC acres vs TMDL estimates

2. On-the-Ground Reality Check

- Revised drainage boundaries
- Connected vs disconnected IC
- Retrofit potential

3. Bean Counting

 Do IC reductions = improved biota?






Mapping Analysis

 Original IC estimates based on 2002 ISAT and land use coefficients

 Revised IC based on GIS measurements 2008 aerials

		IC Acres		
3100-19-1	BASIN NUMBER	TMDL	Direct measure GIS	
	3100-19-1 (Upper)	126	194	
K	3100-19-1-L1 (Swan Lake)	3.6	6.4	
3100-19-2-R1	3100-19-2-R1 (Lower)	15.6	14.9	





On-the-Ground Reality Check

 Revisions to drainage boundaries changes TMDL DA and IC assumptions

 Swan Lake may not be in watershed

BASIN NUMBER

3100-19-1 (Upper)

3100-19-1-L1 (Swan Lake)

3100-19-2-R1


(Lower)

D	A Acres			
TMDL	Field Verification	L-0.25		$\langle \gamma \rangle$
900	876			
13	18			
312	305			
	TOTAL STATE OF	But to the state of the	W. S. W. W. W. W.	THE WAR

NEIWPCC May 17-19, 2010

On-the-Ground Reality Check

- What counts as "disconnected" IC?
 - Drains to pervious area
 - Managed by existing BMP
 - WQ vs runoff reduction
- 51 IC acres already disconnected in "upper" subbasin






What is "effective" pervious cover?







	Existing Conditions			
Eagleville Brook Watershed	TMDL Estimated	GIS Measured	Field Adjusted	
Watershed DA (acres)	1225	1225	1199°	
Watershed IC (acres)	145ª	216 ^b	165 ^d	
% Watershed IC	12%	18%	14%	
11% IC TMDL target (acres)	135	135	132	
Remaining IC to manage (acres)	10	81	33	

Eagleville Brook Watershed	Existing Conditions			
Upper "Basin" 3100-19-1	TMDL Estimated	GIS Measured	Field Adjusted	
3100-19-1 DA (acres)	900	900	876°	
3100-19-1 IC (acres)	126ª	194 ^b	143 ^d	
% IC	14%	22%	16%	
11% IC TMDL target (acres)	99	99	96	
Remaining IC to manage (acres)	27	95	47	

^a IC estimated using land use coefficients and 2002 ISAT data


^b IC measured from GIS mapping of 2008 high resolution imagery

^c Field assessment revealed areas that did not drain to Eagleville Brook

^d Field assessment identified 51 acres of watershed IC was already disconnected and should not be considered "effective."

On-the-Ground Reality Check

- 50 sites visited
- 110 individual retrofits identified
- 127 IC acres potentially managed
- Met with UConn planners, researchers, facility managers
- Link with Master Plans and Landscaping
- Rank "top 10" projects
- 25% design concepts to manage 32 IC acres




Retrofits Types

- Bioretention
- Swales
- Tree planters/ filters
- Gravel-based wetland
- Sand filter
- Green roofs
- Cisterns
- Pervious pavement
- Soil Amendments









Ranking factors: TOP 10

- Amount of IC removed/ disconnected
- Integration with other campus planning/improvements
- Use of different LID practices
- Distribution across campus (location and use, e.g., academic buildings, dorms, parking lots)
- Feasibility (timeline & cost)
- WQ benefits beyond just reduction of volume







Bean Counting

1. Volume Reduction

- Stream volume monitoring at downstream weir
- Runoff reduction estimates as retrofits occur
- Possible runoff red. modeling by UConn Engineering Dept.

2. Impervious Cover Mitigation

- IC removed (pervious lots)
- IC disconnected (bioretention)
- % credits depending on practice?

3. Beyond Volume & Cover

- Water quality projects (gravel wetland, pollution prevention)
- Rehabilitate & plant trees
- Rehabilitate soils
- Restore stream buffers

4. Back to the Bottom-Line Bugs





Table 2.	Table 2. Project Benefits Summary							
	Impervious Cover Drainage Area Treated (acres)	Watershed Treated (%)	TP Removed (lb/yr)	TN Removed (lb/yr)	TSS Removed (lb/yr)	Runoff Reduction (cf)		
High Priority Projects	31.88	2.6	33	207	6,433	18,881		
All Projects	127.19	22	72	517	14890	55,167		





Eagleville Brook Watershed	Existing	Future IC with Retrofit Implementation		
	Conditions*	"Top 10" Projects	All Projects	
Watershed DA (acres)	1199	1199	1199	
Watershed IC (acres)	165	133**	38***	
% Watershed IC	14%	11%	3.2%	
11% IC TMDL target (acres)	132	Tanget met	Target	
Remaining IC to manage (acres)	33	Target met	exceeded	

Eagleville Brook Watershed	Existing	Future IC with Retrofit Implementation			
Upper "Basin" 3100-19-1	Conditions*	"Top 10" Projects	All Projects		
3100-19-1 DA (acres)	876	876	876		
3100-19-1 IC (acres)	143	111**	16***		
% IC	16%	13%	2%		
11% IC TMDL target (acres)	96	Torget not met	Target		
Remaining IC to manage (acres)	47	Target not met	exceeded		

- Using field adjusted watershed DA and IC values
- ** Projects manage a total of 32 acres IC (subtract from 143 acres)
- *** Projects manage a total of 127 acres IC (subtract from 143 acres).

 Assumes B7g option 1; Discounts C15 (already completed) and double treatment by A2.



Implications for Others?

- Setting IC targets
 - Others in Region 1 (ME, CT...)
 - Swift Creek, NC has a 9% IC Target
 - What are protocols for establishing existing and "effective" IC?
- How do new NPDES permit requirements for MA and NH MS4s relate (e.g., tracking IC and DCIA, retrofit inventories of municipal properties)?
- What if not enough on-the-ground opportunities?
 - Lack of publicly-owned properties
 - No single large land owner like UConn
- Elevates LID as a preferred approach to stormwater management in impaired (and non-impaired) waters



Questions???



Anne Kitchell (508)833-6600

akitchell@horsleywitten.com Horsley Witten Group, Inc

Chris Bellucci (860)424-3735

christopher.bellucci@ct.gov
Department of Environmental Protection
Bureau of Water Protection and Land Reuse

Chet Arnold (860)345-5230

chester.arnold_jr@uconn.edu
Department of Extension
Center for Land Use Education and Research
University of Connecticut

http://clear.uconn.edu/eagleville/Eagleville TMDL